

M2552  
**Burris**

## MATERIAL SAFETY DATA SHEET

FOR PRESSURIZED PRODUCTS

<b>HEALTH</b>
2
<b>FLAMMABILITY</b>
4
<b>REACTIVITY</b>
0
<b>PERSONAL PROTECTION</b>
B

**SECTION I**

**MANUFACTURER NAME:**  
Burris

**ADDRESS (Number, Street, City, State and Zip Code):**  
7047 Kearny Drive  
Huntington Beach, CA 92648

**TYPE OF PRODUCT:** TDS SOFTENER      **TRADE NAME:** BURRIS      **PRODUCT CODE:** OP-2 QuickTime 2

**SECTION II HAZARDOUS INGREDIENTS**

INGREDIENT CHEMICAL NAME	TYPE OF HAZARD(S)	TLV	CAS NUMBER
ISOBUTANE PROPANE	FLAMMABLE	500 PPM	68476-88-7
AROMATIC SOLVENT	FLAMMABLE	100 PPM	1330-20-7
ALIPHATIC SOLVENT	FLAMMABLE	500 PPM	110-84-3
AROMATIC SOLVENT	FLAMMABLE	100 PPM	105-85-3
SEAL SWELL ADDITIVE	INHALATION	N.A.	N.A.
GLYCOL ETHER	INHALATION	N.A.	N.A.

**WARNING:** This product contains chemical(s) known to the State of California to cause cancer, birth defects and other reproductive harm.

**SECTION III A: PHYSICAL DATA/ CONTENTS WITHOUT PROPELLANT**

FLASH POINT BELOW 25 F.      SPECIFIC GRAVITY(N20 = 1) 1.21      PH N/A

% VOLATILE BY WGT. 84%      VAPOR DENSITY(AIR = 1) GREATER(X) / LESSER( )      EVAPORATION RATE (N20 = 1) GREATER(X) / LESSER( )

SOLUBILITY IN WATER: INSOLUABLE      APPEARANCE AND ODOR: SOLVENT ODOR/ CLEAR

**SECTION III B: PHYSICAL DATA/ PACKAGED PRODUCT WITH PROPELLANT**

VAPOR PRESSURE @ 70 F.= 48-50 PSIG      VAPOR PRESSURE @ 130 F.= 81 PSIG

FLAMMABILITY CLASS: FLAMMABLE      CONTAINER TEST: POSITIVE(X) / NEGATIVE( )

FLAME EXTENSION @ 70 F.: 12 INCHES      FLASHBACK YES( ) / NO(X)      SPRAY PATTERN: WEB SPRAY

**SECTION IV: FIRE AND EXPLOSION HAZARD DATA**

EXPOSURE TO TEMPERATURES OVER 120 F. (49 C.) MAY CAUSE BURSTING OR VENTING. KEEP CONTAINER COOL. USE EQUIPMENT OR SHIELDING TO PROTECT PERSONNEL AGAINST BURSTING OR VENTING CONTAINERS. DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT SHIP PRODUCT BY AIR.

UNUSUAL FIRE AND EXPLOSION HAZARDS: DO NOT USE NEAR SPARKS, OPEN FLAME OR WHILE SMOKING

EXTINGUISHING MEDIA: WATER FOG(X)      STANDARD FOAM(X)      CO2(X)      DRY CHEMICAL(X)      HALON( )

**SPECIAL PRECAUTIONARY STATEMENTS:** PLEASE READ AND FOLLOW THE DIRECTIONS ON THE PRODUCT LABEL. PLEASE NOTE THAT THE INFORMATION CONTAINED HEREIN IS INFORMATION RECEIVED FROM OUR RAW MATERIAL SUPPLIERS AND OTHER SOURCES AND IS BELIEVED TO BE RELIABLE.

## SECTION V: HEALTH HAZARD DATA

MOST TOXIC INGREDIENT: ACGIH TWA 100.00 PPM / OSHA PEL (TWA) 100.00 PPM / ACGIH STEL 150.00 PPM OSHA STEL 150.00 PPM

## EFFECTS OF OVEREXPOSURE

INGESTION: NAUSEA

EYES: IRRITATION

INHALATION: ANESTHETIC

SKIN: MINOR IRRITATION

## EMERGENCY AND FIRST AID PROCEDURES

INGESTION: DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION.

EYES: FLUSH WITH WATER FOR A MINIMUM OF FIVE MINUTES.

INHALATION: REMOVE TO FRESH AIR. CALL A PHYSICIAN. IF BREATHING STOPS, GIVE MOUTH TO MOUTH RESUSCITATION.

SKIN: WASH WITH WATER.

## SECTION VI: REACTIVITY DATA

CONDITION TO AVOID: DO NOT STORE ABOVE 120 F. (48 C.) AVOID EXPOSURE TO SPARKS, OPEN FLAME, HEAT OR OTHER SOURCES OF IGNITION.

## SECTION VII: SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE LARGE AMOUNTS ARE RELEASED: MOP, SOAK UP OR WIPE UP IMMEDIATELY. PROVIDE VENTILATION.

WASTE DISPOSAL METHOD: DO NOT PUNCTURE OR INCINERATE EMPTY OR FULL GANS. ONCE SPILLS OR LEAKS ARE CLEANED UP, DISPOSE OF WASTE IN ACCORDANCE WITH GOVERNMENTAL ORDINANCES.

## SECTION VIII: IN USE/ SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: ADEQUATE VENTILATION IS REQUIRED. AVOID PROLONGED OR REPEATED BREATHING OF VAPORS.

VENTILATION: RECOMMENDED CROSS FLOW LOCAL EXHAUST: ADEQUATE

PROTECTIVE GLOVES: REQUIRED FOR PROLONGED CONTACT

EYE PROTECTION: SOLVENT RESISTANT

OTHER PROTECTIVE EQUIPMENT: NORMAL PROTECTIVE CLOTHING. WASH HANDS AFTER USE.

## SECTION IX: SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING. DO NOT STORE WHERE TEMPERATURE COULD EXCEED 120 F.

OTHER PRECAUTIONS: SHIP VIA GROUND TRANSPORTATION ONLY. READ AND FOLLOW LABEL DIRECTIONS.